



Splice Closure

Horizontal In-line

Max. capacity 48 fibres

This type of closure has a max. capacity of 48 fibres, placed in four splice trays (12 fibres each). Its main body is resistant to UV and other extreme environmental conditions.

Features:

- Advanced internal structure design
- Enough space inside for winding and storing fibres
- Fibre optic splice trays can be fix together in slide-in-lock and with a opening angle of almost 90°.
- Easy and fast increment or reduction of splice trays.
- Elastic integrated seal fitting

Applications:

- Suitable for bunchy fibres
- Wall-mounting, pole-mounting and aerial

HORIZONTAL IN-LINE SPLICE CASE CLOSURE	
Fibres capacity	48
Colour	Black
Dimensions (mm)	280 x 200 x 90
Nominal weight (kg)	1.2 ~ 1.5
Splice trays capacity	4
Max. of fibres per splice tray	12
Cable diameter range (mm)	8 ~ 14
Cable ports	2
Recommended splice trays	LM-CHR24
Splice protection type	Heat shrinkable 40 - 50 - 60 (mm)
Sealing method	Mechanical
Pressurisation	N / A
Ground terminal	Optional
Sealing	IP65
Temperature (°C)	-40 ~ 65
Standards	IEC 60529
Part Number	LM-H048

Rel. 2-EN/MAY21

www.lightmax.com

Lightmax S.L. reserves the right to change the characteristics in this document without prior notice. This document is property of Lightmax S.L. Redistribution is not allowed without consent of Lightmax S.L.


LightMax[®]
THE FIBRE OPTIC BRAND



LM-CHR24



[Pictures for reference purposes only]



Structural Drawing

