



Patch Panel 1U Sliding rails

2 modular plates | Colour Black

Available: Empty and Equipped

(Up to 48 Fibres)

Part number (empty): 24-SR1U-PLA

[More information](#)

Technical specifications

- Length: 436 mm
- Height : 44 mm
- Depth: 240 mm
- Weight: 3.9 kg (before packaging)

[Pictures for reference purposes only]

Part number (equipped): PPKSR1SC012LCPQXSL012SCUSXME2B6

Product description

Experience state-of-the-art organisation and protection for your fibre optic networks with **LightMax**[®]'s new 1U Patch panel. This all-in-one solution, with capacity for 24 duplex SC adapters and two splice cassettes, offers efficient fibre management, robust protection against environmental damage and a modular design for unlimited scalability. Maximise space in racks and cabinets with the compact 1U design and improve cable protection with its front cable management accessory.

Contact us today to find out more.

Technical specifications

Cassette capacity:	Two splice cassettes (48 fibres)
Plate capacity:	Two modular plates
Material:	Black cold-rolled steel
Protections:	Rear and front
Compatibility:	LC-Dx/Qx Sc Sx/Dx
Protections:	Front support (optional)

Available Configurations

Fibre count	Number and colours of SC Duplex adapters		
	MM	SM	Number of Blind stoppers
12	6 x SCP	6 x SCU	18
24	12 x SCP	12 x SCU	12
48	24 x SCP	24 x SCU	-

Part numbers

Part number	Compatible modular plates
PLA12SCSW	12 · SC/LC · SIMPLEX/DUPLEX · BLACK
PLA12SCDW	12 · SC · DUPLEX · BLACK
PLA18STSW	18 · FC/ST · SIMPLEX · BLACK

Part number	Product
24-SR1U-PLA	PATCH PANEL (EMPTY)
LM-CSR24	SPLICE CASSETTE
48-1U-FSSR	FRONT BRACKET (OPTIONAL)

Application

- Data center
- Enterprise networks
- 5G Telecom facilities

Features

- Front cable management bracket (accessory)
- Includes side cable organisers
- Compatible splice tray: LM-CSR24



[Pictures for reference purposes only]

Part number: LM-CSR24



[Pictures for reference purposes only]

Part number: LM-CSR24