



Closure Box [ONT]

Indoor Termination - 2 Ports

SC Simplex Short Flange

Without adaptors (*)

LightMax® HO2SCSCC Subscriber Termination Box has been developed for FTTX applications. It is used to connect the drop cable and ONU devices. It can handle 2 cores with support for splicing or mechanical connections in wall mounted installation.

Features

- Reduced weight and dimensions.
- Indoor rated.
- Max. capacity: 2 splices.
- Integrated splice tray
- Made of ABS.
- Easy use and installation.
- 2 SC simplex adaptors capacity.
- No flange adaptors.

Applications

- FTTX end termination.

SPECIFICATIONS

Max. capacity	—	2 splices
Colour	—	White
Material	—	ABS
Dimensions	mm	80 x 100 x 23
Cable size	mm	2, 3, 2x3
Nominal weight	kg	0.07
Splice trays count	—	1
Suitable cable	—	Indoor cable Drop cable
Temperature	°C	-40 ~ 85
Protection grade	—	IP30
Wiring methode	—	N/A
Adaptors	—	No flange SC LC duplex
Sealing method	—	N/A
Standards	RoHS 3	

Part Number

LM-HO2SCSCC

Rel. 3-EN/JUL22



(*) Adaptors not included

[Pictures for reference purposes only]

Structural Drawing

