



Closure Box [ODB]

Indoor Distribution

Up to 24 fusions

SC Simplex

LightMax[®] H08SC Distribution Box is suitable for jointing fibre cables and pigtails, helping in fibre distribution and splices protection. This termination box fits either on wall-mounting or desktop type installation, mainly used in telecommunication and network equipment rooms.

Features

- Light weight.
- Small size.
- Easy installation.
- Splice, cable and pigtail protection.
- Made of ABS.
- Equipped with slide-in-lock fibre optic splice tray
- Installation accessories included.
- Up to 24 fusions capacity.
- LM-CHI24 splice tray included.
- IP30.
- RoHS 3.

Applications

- FTTH access networks
- Telecommunications networks
- Data communications networks



[Pictures for reference purposes only]



Inside details



SPECIFICATIONS		
Max. fusions capacity	—	24
Colour	—	Gray
Material	—	ABS
Dimensions	mm	264 x 154 x 56
Splice tray	mm	LM-CHI24 (included)
Nominal weight	kg	0.75
Splice trays count	—	2
Cable diameter range	mm	16 max (inlet) 2, 3, 2x3 (drop)
Temperature	°C	-40 ~ 85
Protection grade	—	IP30
Cable ports	—	4 (inlet) + 12 (outlet for drop)
Adapters	—	SC simplex / LC duplex not included
Sealing method	—	None
Standards	RoHS 3	

LM-H08SC with adaptor plate



LM-H08SC included accessories



[Pictures for reference purposes only]

Part Number

LM-H08SC

Rel. 5-EN/AUG22