



Closure Box [ONT]

Indoor Termination - 4 Ports

SC Simplex - Short flange

Without adaptors (*)

LightMax[®] H04SCSCC Subscriber Termination Box has been developed for FTTX applications. It is used to connect the drop cable and ONU devices. It can handle 4 cores with support for splicing or mechanical connections in wall mounted installation.

Features

- Reduced weight and dimensions.
- Indoor rated.
- Max. capacity: 4 fusions.
- Integrated splice tray
- Made of ABS.
- Easy to install and disassemble.
- 4 SC simplex adaptors capacity.
- No flange adaptors.
- RoHS 3 compliance.
- Rail DIN installation compatibility.

Applications

- FTTX end termination.

SPECIFICATIONS		
Max. capacity	–	4 fusions
Colour	–	White
Material	–	ABS
Dimensions	mm	100.6 x 80.6 x 28.8
Cable size	mm	3.0 x 2.0
Nominal weight	g	90
Splice trays count	–	1
Suitable cable	–	Indoor cable Drop cable
Temperature	°C	-40 ~ 85
Protection grade	–	IP00
Wiring methode	–	N/A
Adaptors	–	No flange SC
Sealing method	–	N/A
Standard	–	RoHS 3.0

Part Numbers

LM-H04SCSCC
LM-H04SCSCCA

Rel. 3-EN/JUL22



(*) Adaptors not included

(*)

[Pictures for reference purposes only]

Structural Drawing

